



GENERAL NOTES:

- 1) UNITS ARE AVAILABLE IN STANDARD SIZES LISTED
(CUSTOM SIZES ARE NOT AVAILABLE)
- 2) ROOF PITCH REQUIREMENTS FOR SKYLIGHTS VARY WITH LOCAL BUILDING CODES FOR HURRICANE SPECIFIC CONSTRUCTION APPLICATIONS. MIN. UNIT PITCH NOT LESS THAN 3:12 IS REQUIRED FOR ANY APPLICATION. CONSULT LOCAL CODES FOR SPECIFIC USE GROUP CRITERIA.
- 3) ROUGH OPENING OF CURB BASED ON MIN. 1 1/2" CURB WIDTH (BY OTHERS)
- 4) GSHR UNIT CARRIES A MIAMI-DADE NOA #04.0728.03 EXPIRATION OCTOBER 20, 2010 AND FLORIDA BUILDING CODE PRODUCT APPROVAL #FL6950
- 5) ROOF FRAMING AND SURFACE CONSTRUCTION SHOWN IN DETAILS ARE FOR REFERENCE ONLY. ROOFING REQUIREMENTS ARE DICTATED BY LOCAL BUILDING CODES AND ARE THE RESPONSIBILITY OF THE BUILDER.

MODEL	R.O. OF CURB*	O.D. OF CURB
2222	22 1/2" X 22 1/2"	25 1/2" X 25 1/2"
2246	22 1/2" X 46 1/2"	25 1/2" X 49 1/2"
3046	30 1/2" X 46 1/2"	33 1/2" X 49 1/2"
4646	46 1/2" X 46 1/2"	49 1/2" X 49 1/2"



WASCO PRODUCTS, INC.

22 PIONEER AVENUE, SANFORD, MAINE 04073
(207) 324-8060, FAX (207) 490-5271

**GSHR HURRICANE
CURB MOUNT
SKYWINDOW UNIT
PLAN VIEW**

PLN1